

Part Number: SG930VA000/010

Production Date: September, 2021

△0

Installation and Operations instructions for Brake pad set(Front/Rear)

- Thank you for purchasing this product.
- This manual provides installation and handling instructions for this product, and precautions to be observed.
- Before using this product, be sure to read "Safety Precautions" and use the product properly.
- Keep this manual in a safe place, such as the glove box, and refer to it whenever necessary.

Important precautions are indicated with the following marks. Be sure to observe those precautions.

⚠ Warning	Precautions that you must observe for your safety. [Failure to observe these precautions may result in death or serious injury.]
⚠ Caution	Precautions that you must observe for your safety and for your vehicle. [Failure to observe these precautions may result in damages or accidents.]
* Advice	Information that you should familiarize yourself with. Information that are useful.

- Never attempt to modify this product. This may damage the product and may become cause of serious accidents.
- Be sure to stop the engine during work for safety reasons.
- · Be sure to tighten bolts and nuts firmly.
- · If abnormal noise or vibration occurs while driving, pull over the car immediately to a safe place, and then inspect and re-tighten the attaching bolts. If abnormalities persist, perform inspection and make necessary repairs immediately. If you continue to drive in this condition, damages or accidents may occur.
- Stop using this product immediately it it has defects such as deterioration and breakage, or receives a strong impact, as these conditions impair the product's original performance.
- · Make sure that no part comes in contact with the battery while working.

↑ Caution

- This product does not improve the limit performance significantly. Always drive safely.
- Do not use this product on inapplicable vehicles or for purposes other than it is designed for. Doing so may result in damages or accidents.
- Install this product in accordance with the service manual issued by SUBARU CORPORATION for your model. Also make sure to adhere to the precautions described in this document.
- · If bolts and nuts are not tightened with specified torque while installing this product, they may be damaged or become loose. Make sure to tighten them with the specified torque.
- · After installing this product, the fluid should be replenished or changed at a SUBARU dealer.

*Advice

- SUBARU shall not be held liable for any direct or indirect damage due to failures or other malfunction caused by incorrectinstallation or handling of this product.
- SUBARU does not honor warranty claims for malfunctions of products or vehicles that occur directly or indirectly due to theinstallation of this product.
- Malfunctions of vehicles that could occur due to the installation of this product may not be covered by the SUBARU vehicle warranty.
- When replacing parts with this product, be sure to use genuine SUBARU parts for non-reusable parts, consumables, oil and grease.
- Product specifications are subject to change without notice.
- Installation of this product may cause deterioration in ride comfort or significant changes in driving characteristics.

Installation Procedures

1.Part Number and Applicable Model

Part number	Part name	Applicable Model
SG930VA000	STI BRAKE PAD SET F	WRX STI TYPE A \sim
SG930VA010	STI BRAKE PAD SET R	WRX STI TYPE A \sim

2.Component

Part Name	Qty
Brake pad set (for Front or Rear)	

^{*} Check the number of items included first. If any items are missing or different, contact the place of purchase.

3.Specification

- · Reinforced brake pad (Friction Material: Non-asbestos material)
- •This product may occur more brake dust and decrease the disc life faster than genuine brake pads.
- •Brake noise may increase by installing this product.

4. Precautions During Installation

Marning

- For safety purposes, always turn off the engine and ignition while operating.
- · Always tighten bolts and nuts firmly.

Caution

- •Installation at a SUBARU certified service workshop is recommended for proper fitting and normal functioning of the product.
- For successful installation of this product, be sure to refer to the service manual of the applicable vehicle model issued by SUBARU CORPORATION and follow all precautions explained herein.
- When working on the vehicle, if nuts and bolts are tightened exceeding the specified torque, they may break or become loose. Make sure to adhere to the specified torque when tightening nuts and bolts.

5.Installation procedure

•Be sure to refer to the service manual (Brake) of the applicable vehicle model issued by SUBARU CORPORATION and follow all precautions explained herein.

Caution

- •The brake pad shim should be reused.
- •Make sure to use genuine Subaru brake grease.
- Grease (Part number: K0777YA000)
- •MOLYKOTE® M7439 (Part number: 003602001)
- -MOLYKOTE® AS880N (Part number: K0777YA010)

To customers

Handling Precautions

⚠ Caution

- •Installation at a SUBARU certified service workshop is recommended for proper fitting and normal functioning of the product.
- •This product is a reinforced brake pad, therefore the brake dust may increase and brake noise may occur.