

2026 Camry HV Pre-Delivery Service (PDS)

Service Category General

Section Pre-Delivery Service

Market USA

Toyota Supports
ASE Certification 

Applicability

YEAR(S)	MODEL(S)	ADDITIONAL INFORMATION
2026	Camry HV	

REVISION NOTICE

May 11, 2026 Rev2:

- The Introduction, Required Tools & Equipment, and D/C Cut Fuse Installation sections have been updated.
- The Customize ACC Function has been removed.

September 29, 2025 Rev1:

- The Required Tools & Equipment section has been updated.

Any previous printed versions of this bulletin should be discarded.

2026 Camry HV Pre-Delivery Service (PDS)

Introduction

Pre-Delivery Service (PDS) is a critical step in satisfying our new car customers. Customer feedback indicates the following areas deserve special attention when performing PDS:

- Careful inspection for paint chips/scratches and body dents/dings.
- Proper operation of electrical accessories (including interior light, clock, and radio reset).
- Interior cleanliness.
- Proper function of mechanical systems.

The PDS process helps identify potential vehicle concerns before customer delivery. After completing the PDS process, maintain accurate PDS records by ensuring the required documents listed below are completed and recorded in accordance with Toyota Warranty Policy.

- GTS+ Health Check
- Completed PDS Check Sheet
- Battery Charge Test Print Out
- GTS+ Tire Pressure Information

Customer retention and proper maintenance of vehicles are, and have always been, a major focus for Toyota. To help remind customers that regular service is essential to the proper maintenance of the vehicle, dealers are required to install a service reminder sticker before delivery. By doing this, customers will be reminded to return to your dealership for service. Your current service reminder sticker may be used. (See PDS *Check Sheet* item 7 of “Final Inspection and Cleaning.”)

2026 Camry HV Pre-Delivery Service (PDS)

Introduction (continued)

This bulletin contains the PDS procedures that apply specifically to 2026 model year Camry Hybrid vehicles.

Refer to [T-SB-0023-25](#), the universal *Check Sheet* that contains PDS steps that apply to all 2026 model year Toyota vehicles. To properly perform a complete PDS, you must complete all procedures contained in this TSB as well as the universal PDS *Check Sheet*. In addition, if the vehicle is stored for over 30 days, refer to [T-SB-0002-26](#), *Long-Term Vehicle Storage Guidelines*.

Refer to the table below for a definition of terms that may be used in this bulletin.

Table 1.

TERM	ACRONYM	DEFINITION
Conventional Vehicle	CV	A vehicle with only a gasoline engine for propulsion
Electrified Vehicle	EV	A vehicle that utilizes a hybrid, plug-in hybrid, fuel cell, or battery electric system for propulsion
Hybrid Electric Vehicle	HEV	A vehicle with both a gasoline engine and an HV battery
Plug-in Hybrid Electric Vehicle	PHEV	A vehicle with both a gasoline engine and an HV battery that can be charged externally
Battery Electric Vehicle	BEV	A vehicle with only an HV battery that can be charged externally
Fuel Cell Electric Vehicle	FCEV	A vehicle with both a hydrogen fuel cell and an HV battery
State of Charge	SOC	The remaining capacity available in a battery
12-Volt	12V	Standard 12V battery used to power electrical systems separate from high voltage components
High Voltage	HV	HV battery used to power the electrified vehicle

2026 Camry HV Pre-Delivery Service (PDS)

Table of Contents

• Warranty Policy	5
• Warranty Information	5
• Required Tools and Equipment	5
• D/C Cut Fuse Installation	6
• Front License Plate and Mounting Bracket Installation *	7
• Installation Procedure (Type A)	7
• Installation Procedure (Type B)	8
• Front Wheel Opening Extension Pad Installation	9
• Check Torque of Wheel Fasteners	10
• Tire Pressure Warning System (TPWS) Initialization	10
• Seat Position Control ECU Initialization	10
• Head Unit System Reset	11
• Dealer Contact Information for Call Dealer Head Unit Function	11
• Navigation — Set Date & Time by GPS	11

*If applicable.

2026 Camry HV Pre-Delivery Service (PDS)

Warranty Policy

If the need for additional repairs or adjustment is noted during PDS, the required service should be performed under warranty. Reimbursement will be managed under the warranty policy.

The Warranty Policy and Procedures Manual requires that you maintain the completed Check Sheet in the customer's file. If you cannot produce a completed form for each retailed vehicle upon TMS and/or Region/Distributor audit, the PDS payment amount will be subject to debit.

An additional Repair Order completed in conjunction with normal PDS MUST have time punch/flags for service. If multiple repairs are performed, separate time flags MUST be punched for each repair.

Warranty Information

OP CODE	DESCRIPTION	MODEL	TIME	OFP	T1	T2
001013	Pre-Delivery Service (PDS)	Camry HV	1.5	–	–	–

Required Tools & Equipment

REQUIRED EQUIPMENT	SUPPLIER	PART NUMBER	QTY
Techstream ADVi*	ADE	TSADVUNITECP	1
Techstream Lite		TSLP3DLR01	
Techstream Lite (Green Cable)		TSLP2DLR01	

*Essential SST.

NOTE

- Only ONE of the Techstream units listed above is required.
- GTS+ software version 2026.01.003.02 or later is required.
- Additional Techstream units may be ordered by calling Approved Dealer Equipment (ADE) at 1-800-368-6787 or by visiting *TIS – Diagnostics – Tools & Equipment – Techstream Order Portal*.


2026 Camry HV Pre-Delivery Service (PDS)

D/C Cut Fuse Installation

Check the location of the D/C Cut fuse (30A). It may have been removed at the assembly plant and temporarily stored in the blank space of the relay block in the engine compartment to minimize battery discharge during transportation and storage.

- If the D/C Cut fuse (30A) is still in its original location in the relay block, proceed with performing a Health Check using GTS+.
- If the D/C Cut fuse (30A) is NOT in its original location, it is necessary to remove the D/C Cut fuse (30A) from the blank space in the relay block and reinstall it to its original location as shown. After installation, confirm ALL related DTCs are cleared.

Figure 1.



1	Relay Block
2	Remove the D/C Cut Fuse (30A) (Blank Space)

3	Install the D/C Cut Fuse (30A) (Original Location)
---	--

NOTE

- With the D/C Cut fuse (30A) removed, if ANY DTCs are detected when the ignition is turned ON during transportation, use GTS+ to clear ALL DTCs AFTER ensuring that there are NO malfunctions.
- While the vehicle is stored at the dealership, disconnect the negative (–) battery terminal to prevent battery discharge. Refer to [T-SB-0005-26](#), *Battery Inspection and Maintenance During PDS*, for battery maintenance information.

2026 Camry HV Pre-Delivery Service (PDS)

Front License Plate and Mounting Bracket Installation

The front license plate mounting bracket set (front license plate mounting bracket, two or four long self-tapping screws, and two short self-tapping screws) is loaded in the luggage compartment at the assembly plant. Follow this procedure to install the front license plate bracket and front license plate in states where it is required by law.

Installation Procedure (Type A)

1. Align the holes on the front license plate mounting bracket with the dimples on the front of the lower grille.
2. Install the four long self-tapping screws through the slotted and round holes on the front license plate mounting bracket into the lower grille.

NOTICE

- Do NOT pre-drill holes through the lower grille.
- Do NOT overtighten the self-tapping screws.


3. Align the holes on the license plate with the corresponding holes of the front license plate mounting bracket.
4. Install the two short self-tapping screws through the holes on the front license plate mounting bracket and license plate.

Dimensions:

Long self-tapping screw length:
37 mm (1.456 in.)

Short self-tapping screw length:
16 mm (0.630 in.)

Figure 2.



1	Dimples
2	Front License Plate Mounting Bracket
3	Long Self-tapping Screws
4	Short Self-tapping Screws
5	Front License Plate

2026 Camry HV Pre-Delivery Service (PDS)

Front License Plate and Mounting Bracket Installation (continued)

Installation Procedure (Type B)

1. Align the holes on the front license plate mounting bracket with the dimples on the front of the lower grille.
2. Install the two long self-tapping screws through the slotted and round holes on the front license plate mounting bracket into the lower grille.

NOTICE

- Do NOT pre-drill holes through the lower grille.
- Do NOT overtighten the self-tapping screws.


3. Align the holes on the license plate with the corresponding holes of the front license plate mounting bracket.
4. Install the two short self-tapping screws through the holes on the front license plate mounting bracket and license plate.

Dimensions:

Long self-tapping screw length:
37 mm (1.456 in.)

Short self-tapping screw length:
16 mm (0.630 in.)

Figure 3.



1	Dimples
2	Front License Plate Mounting Bracket
3	Long Self-tapping Screws
4	Short Self-tapping Screws
5	Front License Plate

2026 Camry HV Pre-Delivery Service (PDS)

Front Wheel Opening Extension Pad Installation

The front wheel opening extension pad set (right and left front wheel opening extension pads) is loaded in the luggage compartment at the assembly plant to avoid damage in transit.

1. Remove the three self-tapping screws from the engine under cover.

HINT

The removed self-tapping screws are reused when installing the front wheel opening extension pad.


2. Place the left front wheel opening extension pad on the installation position as shown and tighten the three self-tapping screws.

HINT

There is a distinguishable mark on each pad.

3. Repeat steps 1 and 2 for the right-hand side.

Figure 4.



1	Remove the Self-tapping Screws
2	Front Wheel Opening Extension Pad
3	Install the Self-tapping Screws

2026 Camry HV Pre-Delivery Service (PDS)

Check Torque of Wheel Fasteners

Using a calibrated torque wrench, verify the wheel fasteners on each wheel are tightened to at least the specified torque listed in the Repair Manual.

- [2026](#) Camry HV:
General – Maintenance – Tire and Wheel – Installation

NOTICE

Do NOT continue to tighten once verified.

Tire Pressure Warning System (TPWS) Initialization

Refer to the applicable Repair Manual for the TPWS initialization procedure.

- [2026](#) Camry HV:
Suspension – Tire Pressure Monitoring – Tire Pressure Warning Receiver – Initialization

NOTE

- To adjust the tire pressure correctly when the outside temperature is significantly colder than shop temperature, perform a Health Check using GTS+ and select the compensation tire pressure checkbox. Compensation pressures will display on the Health Check results screen. Adjust the tire pressure when the tires are cold.
- This model has four TPWS sensors.

Seat Position Control ECU Initialization

Refer to the applicable Repair Manual for the seating position control ECU Initialization procedure (procedure 2).

- [2026](#) Camry HV:
Vehicle Interior – Seat – Front Power Seat Control System (w/ Memory) – Registration

2026 Camry HV Pre-Delivery Service (PDS)

Head Unit System Reset

Prior to vehicle delivery, confirm that the welcome screen with language options appears on the head unit display when the ignition is switched to the ON position. There may be instances where the welcome screen with language options may not properly appear on the head unit display.

If the welcome screen showing language options is not displayed, complete the following steps:

1. Select the Settings option (gear icon).
2. Scroll down and select the Info & Security option.
3. The System Reset dialogue box will appear. Select Reset to confirm the resetting of the system.
4. Confirm that the welcome screen with language options is now displayed.

Dealer Contact Information for Call Dealer Head Unit Function (Premium Audio Only)

Refer to the *Multimedia System Owner's Manual* to add dealer contact information.

- [2026](#) Camry HV:
Section 2-8 *Vehicle Settings – Setting Dealer Information*

Navigation — Set Date & Time by GPS

Prior to vehicle delivery, it is necessary to turn the Set date & time by GPS setting to the ON position.

1. Turn the engine switch (power switch) to the ON position (ON mode).
2. Navigate the following menus in the head unit: *Settings – General – Date & Time – Set Date & Time by GPS*.
3. Ensure the Set date & time by GPS function is set to the ON position.