

Tire Positioning Before New Vehicle Delivery

Service Category General

Section Pre-Delivery Service

Market USA

Toyota Supports
ASE Certification 

Applicability

YEAR(S)	MODEL(S)	ADDITIONAL INFORMATION
2026	4Runner, 4Runner HV, 86, bZ, bZ Woodland, C-HR BEV, Camry HV, Corolla, Corolla Cross, Corolla Cross HV, Corolla Hatchback, Corolla HV, Crown, Crown Signia, GR Corolla, Grand Highlander, Grand Highlander HV, Highlander, Highlander HV, Land Cruiser, Mirai, Prius, Prius PHV, RAV4 HV, RAV4 PHV, Sequoia HV, Sienna HV, Supra, Tacoma, Tacoma HV, Tundra, Tundra HV	

REVISION NOTICE

June 18, 2026 Rev1:

- Applicability has been updated to include 2026 model year Mirai vehicles.
- Any previous printed versions of this bulletin should be discarded.

SUPERSESSION NOTICE

The information contained in this bulletin supersedes Service Bulletin No. T-SB-0005-25.

- Applicability has been updated to include 2026 model year C-HR BEV vehicles.
- Applicability has been updated to remove 2026 model year C-HR vehicles.

Service Bulletin No. T-SB-0005-25 is obsolete and any printed versions should be discarded.

Tire Positioning Before New Vehicle Delivery

Introduction

During the manufacturing process, tires are mounted on the vehicle as matched sets to help reduce conditions such as pulling or drifting. If the wheels are replaced or refinished before vehicle delivery, it is important that the tires remain on the vehicle in the same location and in the same direction of rotation.

Refer to the Tire Positioning Procedure in this bulletin to ensure that the original tires stay in the same location on the vehicle.

Warranty Information

OP CODE	DESCRIPTION	TIME	OFP	T1	T2
N/A	Not Applicable to Warranty	—	—	—	—

Tire Positioning Procedure

1. Mark the tire installation position on the inward facing tire sidewall.
Example: Front Right = FR, Front Left = FL, Rear Right = RR, Rear Left = RL
2. Install the original tires on the NEW or refinished wheels with the marked side facing inward.
3. Balance the tire/wheel assemblies.
4. Place the tire/wheel assemblies on the vehicle in the marked positions.

NOTE

Torque the wheel fasteners in sequence to the proper torque value.