

**TIRE AND LOADING INFORMATION**

Seating Capacity: Total: 2 | Front: 2 | Rear: 0  
 The combined weight of occupants and cargo should never exceed 1860 Kgs or 4101 Lbs

SIZE	COLD TIRE PRESSURE	SEE OWNER'S MANUAL FOR ADDITIONAL INFORMATION
225/75R16E	517 kpa 75 psi	
225/75R16E	448 kpa 65 psi	
225/75R16E	517 kpa 75 psi	

**RENSEIGNEMENTS SUR LES PNEUS ET LE CHARGEMENT**

Nombre De Places: Total: 2 | Avant: 2 | Arriere: 0  
 Le poids total des occupants et du chargement ne doit jamais dépasser 1860 Kgs ou 4101 Lbs

DIMENSIONS	PRESSION DES PNEUS À FROID	VOIR LE MANUEL DE L'USAGER POUR PLUS DE RENSEIGNEMENTS
225/75R16E	517 kpa 75 lb/po2	
225/75R16E	448 kpa 65 lb/po2	
225/75R16E	517 kpa 75 lb/po2	

R P M 0 2 5 6 6 9

R P M 0 2 5 6 6 9



1FDWE3F61KD

Dry Weight: 8014 lbs



RPM025669

Dry Weight: 8014 lbs

MANUFACTURED BY / FABRIQUE PAR		FOREST RIVER, INC.		DATE	9/20/2018
V.I.N./I.V.		1FDWE3F61KD	RPAF1266W	RPM025669	
GVWR/PNEV		5670 KG ( 12500 LB)	TRU/CAM		
DESIG. SEAT CAP./NOMBRE D'ESIGNE' DE PLACES ASSISES		2X68kg=136 kg or 2X150lbs=300 lbs			
GVWR/PNEE		TRES/PNEU		RIMS/QUANTE	
FRONT/AVANT	1837 KG 4050 LB	16X6.0K	LT225/75R16E	COLD INFL. PRESS/PRESS. DE GONFL. A FROID	
INTERM/NTERM	0 KG 0 LB			517 KF SINGLE DUAL	75 PSILPC <input checked="" type="checkbox"/>
REAR/ARRIERE	3856 KG 8500 LB	16X6.0K	LT225/75R16E	0 KP SINGLE DUAL	0 PSILPC <input type="checkbox"/>
				448 KP SINGLE DUAL	65 PSILPC <input checked="" type="checkbox"/>

THIS VEHICLE CONFORMS TO ALL APPLICABLE U.S. FEDERAL MOTOR VEHICLE SAFETY STANDARDS IN EFFECT ON THE DATE OF MANUFACTURE SHOWN ABOVE.

THIS VEHICLE CONFORMS TO ALL APPLICABLE STANDARDS PRESCRIBED UNDER THE CANADIAN MOTOR VEHICLE SAFETY REGULATIONS IN EFFECT ON THE DATE OF MANUFACTURE.

CE VEHICULE EST CONFORME A TOUTES LES NORMES QUI UI SONT APPLICABLES EN VERTU DU REGLEMENT SUR LA SECURITE DES VEHICLES AUTOMOBILES DU CANADA EN VIGEUR A LA DATE DE SA FABRICATION.

INC. VEL MFG BY: Ford