



SECTION A-A

NOTE:

1. 16" X 8" SOLID RIM
2. 8 ON 6 1/2 BOLT PATTERN FOR 5/8 STUDS
3. 1/2" POSITIVE OFFSET (TIRE INSET)
4. PAINTED SILVER
5. 3750# LOAD RATING

| | | | | | | | | |
|-----|--------|-----------------------------------|--|--|------------|-------------|----------------------|--|
| | | | | | | B | DO NOT SCALE DRAWING | Approximate Weight = 41.91 lb. |
| | | | | 3RD ANGLE PROJECTION | | 1 PAGE OF 1 | SUB. MATL SPECS | |
| | | | | UNLESS OTHERWISE SPEC. DIMNS. IN INCHES ANSI Y14.5 - 1982 W.P.S 1-1- A-100 STD. TOLERANCES X.X ± .060 X.XX ± .030 X.XXX ± .010 FRAC.DIM. ± 1/32 DEG. ± 1 | | DESCRIPTION | | WHL-16"X 8"SILVER,8 ON 6.5";5/8" STD;1/2 OFFSET ST235/80R16 E |
| B | 112647 | RENAMED FOR BETTER IDENTIFICATION | | SLM | 10/15/2007 | ITEM NUMBER | | 163647345 |
| A | 109969 | PRODUCTION RELEASE | | GSW | 11/30/06 | DESIGN BY | | JJH |
| REV | ECN | CHANGE DESCRIPTION | | CHANGE BY | DATE | DATE | | 11/20/2006 |
| | | | | | | | | NOTICE: THIS DOCUMENT AND ITS CONTENTS ARE THE PROPERTY OF VERMEER MANUFACTURING COMPANY. NO USE OR COPIES MAY BE MADE WITHOUT WRITTEN PERMISSION FROM VERMEER |
| | | | | | | | | |