



MINI COMBO SERIES



MC 573/873 SDT:

MINI COMBO SERIES

Super Diesel Trailer



WWW.VACTRON.COM 1-888-VAC-TRON 822-8766



GENERAL DIMENSIONS AND WEIGHTS - SKID:

Length: 14.75' (4.5m) (573 Model) 16.4' (5m) (873 Model)

Height: 82" (208m)

Empty Weight: 6,855lbs (3,109.4kg) (573 Model) Empty Weight: 7,200lbs (3,265.9kg) (873 Model)

Width: 93" (236cm)

GENERAL DIMENSIONS & WEIGHTS - TRAILER:

Empty Weight: 7,635lbs (3,463kg) (573 Model) Empty Weight: 8,580lbs (3,891.8kg) (873 Model)

Length: 19.25' (5.9m) (573 Model) 22.4' (6.8m) (873 Model)

Width: 93" (236.2cm) Height: 90" (228.6cm) Brake Type: Electric Hitch Type: Pintle

GVWR: 14,000lbs (6,350kg) (573 Model) GVWR: 20,000lbs (9,072kg) (873 Model)

ENGINE:

Horsepower: 83 hp (62kW) Yanmar diesel

Enclosure: Yes

Fuel Tank Capacity: 30gal (114L)

JETTER PUMP:

Water flow: 15gpm Water Pressure: 2,000 psi Jetter hose length: 300' (91m) Jetter hose diameter: 0.5" (1cm)

OPTIONAL BOOM:

Pick up Hose: 4" (10cm) Reach: 15' (5m) Movement: 6-way

WATER TANK:

Water Tank Capacity: 300gal (1,136L) (573 Model) 400gal (1,515L) (873 Model)

Number of Tanks: 2

High Pressure Pump Flow Rate: 15gpm (57 lpm) High Pressure Pump: 2,000psi (140 bar) High Pressure Hose Length: 300' (91m) jetter

50' (15m) high pressure

Low Water Shut Off: Yes

SPOIL TANK:

Spoil Tank Capacity: 500gal (1,893L) (573 Model) Spoil Tank Capacity: 800gal (3,028L) (873 Model)

Door Type: Hydraulic Tank Lift Type: Hydraulic

VACUUM:

Type of Filters: Cartridge filter 0.5 microns

Hose Length: 30' (9m) Hose Width: 3" (8cm)

Optional 4" (10cm)

Vacuum: 1,000cfm

Water Trap Capacity: 60gal (227L) Suction Hose Storage: 30' (9m)

CONTROL PANEL:

Controls: Curbside Gauges: Analog

OPTIONAL STRONG ARM:

Reach: 15' (5m)




CVS FILTRATION HOUSING:

The MC ground level filtration housing also incorporates a 28" (71.1cm) diameter cyclone, four-way valve for reverse pressure, and the largest silencer in the industry for quiet performance. **Patented.**

7 SERIES HYDRAULIC CLAW DOOR:

No fuss, over center locking mechanism for positive lock and unlock.





OPTIONAL BOOM:

Optional six-way hydraulic boom maximizes job performance by supporting the weight of the vacuum hose.

Vac-Tron Equipment, LLC., reserves the right to make changes in engineering, design and specifications; add improvements; or discontinue manufacturing at any time without notice Shown is for illustrative purposes only, and may display optional accessories or components. Please contact your local Vac-Tron dealer for more information on machine specifications. Vac-Tron and the Vac-Tron logo are trademarks of Vac-Tron Equipment.

3 2017 Vac-Tron Equipment, LLC. All Rights Reserved. Printed in the U.S.A. Please Recycle

