



Recall Campaign

NHTSA # 20V-602

October 6, 2020

CHANGING THE FEDERAL CERTIFICATION AND TIRE LABELS

Remove existing label(s)

1. Locate the label(s) on the outside off door side (road side) front of the unit.
2. Using isopropyl alcohol and a shop rag, remove any adhesive residue from the surface where the original label had been. Allow the area to dry for at least 30 seconds.

**The labels below do NOT show the correct information for Recall 20V-602
They are only examples of the different types of labels affected.**

Apply new label(s)

3. Remove the protective back from the new labels. Align the new label in the same location of the original label and apply it to the surface. Remove any air bubbles from the label.

NOTE: Do not attempt to remove or adjust the label once it has come into contact with the surface. Doing so may damage the label or cause it not to adhere properly to the surface. IF A LABEL IS DAMAGED OR WILL NOT PROPERLY ADHERE TO THE SURFACE, PLEASE REQUEST A NEW LABEL at compliance@jayco.com.

*** 1UJBJ0BK2B1J30198 ***

RESP MFR: FABRICANT RESP:	Jayco, Inc.	DATE: 08/10
V.I.N./N.I.V.	1UJBJ0BK2B1J30198	
GVWR /PNBV KG 5500 2497	SIZE/DIMENSION	PRESS. /COLD INFL. PRESS. /GONFL FROID
GAWR/PNBE KG	TIRE/PNEU RIMS/JANTE	PSI/LPC KPA
2900 1317 FRONT/DEVANT	ST185/80R13C 13 X 4.50	JJ 50 345
0000 INT/CENTRAL		0000
2900 1317 REAR/ARRIERE	ST185/80R13C 13 X 4.50	JJ 50 0345
TYPE OF VEHICLE/TYPE DE VEHICULE: TRAILER/REMORQUE		
THIS VEHICLE CONFORMS TO ALL APPLICABLE U.S. FEDERAL MOTOR VEHICLE SAFETY STANDARDS AND STANDARDS PRESCRIBED UNDER THE CANADIAN MOTOR VEHICLE SAFETY REGULATIONS IN EFFECT ON THE DATE OF MANUFACTURE SHOWN ABOVE.		
CE VEHICULE CONFORME A TOUTES LES NORMES QUI LUI SONT APPLICABLES EN VERTU DU REGLEMENT SUR LA SECURITE DE VEHICULES AUTOMOBILES DU CANADA ET DES ETATS UNIS EN VIGUEUR A LA DATE DE SA FABRICATION CI-DESSUS.		

**TIRE AND LOADING INFORMATION
RENSEIGNEMENTS SUR LES PNEUS ET LE CHARGEMENT**

The weight of cargo should not exceed 732 kg or 1612 lbs.
Le poids du chargement ne doit jamais dépasser 732 kg ou 1612 lbs.

TIRE PNEU	SIZE DIMENSIONS	COLD TIRE PRESSURE PRESSION DES PNEUS A FROID
FRONT AVANT	ST225/75R15D	449 KPA, 65 PSI
REAR ARRIERE	ST225/75R15D	449 KPA, 65 PSI
SPARE DE SECOURS	ST225/75R15D	449 KPA, 65 PSI

SEE OWNER'S MANUAL FOR ADDITIONAL INFORMATION
VOIR LE MANUEL DE L'USAGER POUR PLUS DE RENSEIGNEMENTS

15948868302685075

Tire Label

Federal Certification Label