

MOTOR HOME OCCUPANT AND CARGO CARRYING CAPACITY

VIN: [REDACTED]

THE COMBINED WEIGHT OF OCCUPANT AND CARGO SHOULD

NEVER EXCEED: 1144 kg or 2521 lbs

Safety belt equipped seating capacity: 4

CAUTION:

A full load of water equals 154 kg or 340 lbs of cargo @ 1 kg/L (8.3 lb/gal) and the tongue weight of a towed trailer counts as cargo

RECREATIONAL MOTOR HOME CARGO CARRYING CAPACITY

Capacité de transport de chargement d'autocaravane de récréation

CARGO-CARRYING CAPACITY IS DETERMINED WITH THE FRESH WATER TANKS FULL AND THE WASTE TANKS EMPTY

Capacité de chargement est calculée avec les réservoirs d'eau douce pleins et les réservoirs d'eaux usées vides

Dry weight/Poids Sec:	4333 KG	VIN/NIV:	[REDACTED]
Cargo carrying capacity:	989 KG	Capacité de transport de chargement:	989 KG
Calculated with the fresh water tanks full		Calculé avec les réservoirs d'eau douce pleins	
Cold:	132 KG	Froid:	132 KG
Hot:	23 KG	Chaud:	23 KG
Mass of waste water tank		Masses de réservoirs d'eaux usées pleins:	
	252 KG		252 KG



TIRE AND LOADING INFORMATION

Seating Capacity | Total:4 | Front:2 | Rear:2
The combined weight of occupants and Cargo should never exceed 1144 Kgs or 2521 Lbs

TIRE	SIZE	COLD TIRE PRESSURE	SEE OWNER'S MANUAL FOR ADDITIONAL INFORMATION
FRONT	LT225/75R16/E	517 kpa 75 psi	
REAR	LT225/75R16/E	448 kpa 65 psi	
SPARE	LT225/75R16/E	517 kpa 75 psi	



RENSEIGNEMENTS SUR LES PNEUS ET LE CHARGEMENT

Nombre De Places | Total:4 | Avant:2 | Arrière:2
Le poids total des occupants et du chargement ne doit jamais dépasser 1144 Kgs ou 2521 Lbs

PNEU	DIMENSIONS	PRESSION DES PNEUS À FROID	VOIR LE MANUEL DE L'USAGER POUR PLUS DE RENSEIGNEMENTS
AVANT	LT225/75R16/E	517 kpa 75 lb/po2	
ARRIÈRE	LT225/75R16/E	448 kpa 65 lb/po2	
DE SECOURS	LT225/75R16/E	517 kpa 75 lb/po2	

E
A
9
0
5
0
0
0
2



DRY WEIGHT: 9552 LBS
RECREATIONAL VEHICLE OVERALL LENGTH 23'10" AS MANUFACTURED.

MANUFACTURED BY / FABRIQUE PAR: **FOREST RIVER, INC.**
V.I.N./N.I.V.: [REDACTED] **EAC2200SF**
GVWR/PNBV: **5670 KG (12500 LB)** TYPE/TYPE: **MH/AC**

DATE: **5/25/2021**

DESIG. SEAT CAP./NOMBRE' D'ESIGNE' DE PLACES ASSISES **4X68kg=272 kg or 4X150lbs=600 lbs**

GAWR/PNBE	TIRES/PNEU	RIMS/JANTE	COLD INFL. PRESS/PRESS DE GONFL. A FROID
FRONT/AVANT (2268 KG 5000 LB)	LT225/75R16/E	16X6.0K	517 KP SINGLE DUAL (75 PSI/LPC <input checked="" type="checkbox"/> <input type="checkbox"/>
INTERM/INTERM (0 KG 0 LB)			0 KP SINGLE DUAL (0 PSI/LPC <input type="checkbox"/> <input type="checkbox"/>
REAR/ARRIÈRE (3856 KG 8500 LB)	LT225/75R16/E	16X6.0K	448 KP SINGLE DUAL (65 PSI/LPC <input type="checkbox"/> <input checked="" type="checkbox"/>

E
A
9
0
5
0
0
0
2



DRY WEIGHT: 9552 LBS
RECREATIONAL VEHICLE OVERALL LENGTH 23'10" AS MANUFACTURED.

THIS VEHICLE CONFORMS TO ALL APPLICABLE U.S. FEDERAL MOTOR VEHICLE SAFETY STANDARDS IN EFFECT ON THE DATE OF MANUFACTURE SHOWN ABOVE.

THIS VEHICLE CONFORMS TO ALL APPLICABLE STANDARDS PRESCRIBED UNDER THE CANADIAN MOTOR VEHICLE SAFETY REGULATIONS IN EFFECT ON THE DATE OF MANUFACTURE.

CE VEHICULE EST CONFORME A TOUTES LES NORMES QUI UI SONT APPLICABLES EN VERTU DU REGLEMENT SUR LA SECURITE DES VEHICLES AUTOMOBILES DU CANADA EN VIGEUR A LA DATE DE SA FABRICATION.

INC. VEL. MFG. BY: **FORD**