

To All Lamborghini Dealers and Licensed Service Point

From Customer Service Department Subject CCB Fasteners Replacement.

Group 6.15.00 Date 04<sup>th</sup>/10/2013

Pages 15

## **Subject**

**CCB** Fasteners Replacement

#### Model

All Lamborghini Gallardo Coupe and Spyder MY 09 from VIN 9LA06526 to VIN 9LA08928.

<u>Warning:</u> some vehicles included in this VIN range may not be involved, so check carefully on the Lamborghini WEB Portal ( at the section named VIN Info) if the cars in your workshop or in your dealer stock are involved before performing any other operation.

#### Information to the field

As a result of continuous product monitoring, Automobili Lamborghini Spa has found that on vehicles fitted with carbon ceramic discs (CCB) brakes, the stainless steel screws fixing the rotor to the metal bell may fail due to stress corrosion cracking, if the vehicle has been used in extreme salt environments.

#### **Field solution**

Replace the CCB fasteners.

#### **Spare Parts**

P/N	Desc	cription	Q
0R1400661	Fast	asteners Kit	
	Α.	<b>A.</b> Front axle (4F0498998F), 20 little plastic bags containing:	
	1 I	Bolt Q.1	
	2 5	Sleeve Q.1	
	3 1	Nut. Q.1	
	4 \	Washer Q.1	
	В.	Rear axle (4F0498998F), 20 little plastic bags containing:	
	1 I	Bolt Q.1	
	2 5	Sleeve Q.1	
	3 1	Nut. Q.1	
	4 \	Washer Q.1	



## **Replaced Fasteners management**

The replaced items have to be stored with care and tagged with the proper label.

They can be scrapped only with approval of the Service Area Manager in charge and at his presence

## Warranty Claim data

The warranty reimbursement request for this rework action will be managed by the following standard Warranty Claim procedures.

Campaign Code: L71X-R.02.13

Campaign Description: CCB Fasteners replacement

Cost Code: 60


Component Code: CCR0213

**Trouble Code:** 220

Labour Code: CCR0213100

Labour Time: 3h

Remember to fill all data in the section "Service and Recall Campaign" in the Warranty booklet of the vehicle as shown below.





# **Description of required procedures**

## Necessary Tool

1	Torx wrench T80.	TOO_83x13_0000001
2	Wheel insertion tool (P/N 65395009).	TOO_83x13_0000002
3	Torque wrench [0 – 25 Nm]. (P/N 900000329)	MANDATORY / SEND AUTOMATICALLY.

## **Identification**



The information and procedures published below are strictly confidential and intended exclusively for authorized operators and individuals. All copyrights are the property of Automobili Lamborghini S.p.A based on copyright law. The company reserves the right to make updates and modifications. The reprinting, reproduction, forwarding to unauthorized people and/or to third parties and partial or entire translation thereof are prohibited without written authorization from Automobili Lamborghini S.p.A.



#### Checking ceramic brake disc for damage:

- A. Disc inside surface
- B. Disc outside surface

Remove the ceramic brake discs (refer to chapter 06 0703 of Gallardo 09 Workshop Manual).



On vehicles with ceramic brakes the wheel must not be allowed to drop onto the brake disc. This would cause irreparable damage to the disc. Screw two assembly pins (from vehicle tool kit) into the wheel bolt holes when removing and fitting a wheel. Insert the longer assembly pin into the top hole.

4



Please perform a first wear check on brake discs per workshop manual to ensure campaign fullfilment is performed in specification brake discs.

If during the checking it is found that rotors replacement is necessary (conditions are following described) file a Quick claim choosing "technical support" support in Warranty Portal before starting the replacement.

The description of discs condition must be reported in a clear form attaching pictures showing clearly the reason of your request. You will get a quick reply.

The information and procedures published below are strictly confidential and intended exclusively for authorized operators and individuals. All copyrights are the property of Automobili Lamborghini S.p.A based on copyright law. The company reserves the right to make updates and modifications. The reprinting, reproduction, forwarding to unauthorized people and/or to third parties and partial or entire translation thereof are prohibited without written authorization from Automobili Lamborghini S.p.A.




#### A. Outside surface of brake disc

Due to the production process, relaxation cracks already exist on the friction surface of the brake disc when it is new. These cracks can vary in size and can occur on both sides of the disc.

5



Relaxation cracks on a ceramic brake disc do not constitute a technical problem.






Cracks in the cooling channel lands -arrow- are caused during manufacture.

6



Cracks in the cooling channel lands do not constitute a technical problem.




## B. Inside surface of brake disc:

Ceramic brake discs must be replaced if there are cracks in the vicinity of the bolted connection on the inside of the brake disc hub extending into the friction surface of the disc (arrows).

7

Ceramic brake discs must be replaced if there are radial cracks in the area of the bolted connection on the brake disc hub.






Edge fractures -arrow- are caused by mechanical damage to the edges of the disc.

Permissible damage:

- Max. width / depth = 2 mm
- Max. length = 10 mm
- Max. 3 edge fractures per brake disc


If any of the criteria listed above are exceeded, the brake disc must be replaced.

File a Quick claim before replacing.



Ceramic brake discs with cracking extending from the friction surface of the disc to the cooling channel or through the cooling channel must be replaced.

File a Quick claim before replacing.






Ceramic brake discs with chipping larger than 1 cm<sup>2</sup> at any one point -arrow- on the friction surface must be replaced.

**10** 

File a Quick claim befpre replacing.





## **Replacing fasteners**

# 1<sup>st</sup> Option

using the engine and gearbox support (P/N 69195227) and universal adaptor (P/N 69195257).



# If you need engine and gearbox support and/or universal adaptor please order.

After removal, attach the ceramic brake disc either directly to the engine and gearbox support (P/N 69195227) and universal adaptor (P/N 69195257).






## Option 2:

using a spare parts hub (P/N 4D0407613E) as support.



# PLEASE DO NOT USE the vehicle hub, BUT ORDER a NEW ONE (P/N 4D0407613E).

After removal and inspection, attach the ceramic brake to nub (P/N 4D0407613E) as described in the 2 following steps.



Secure the hub (P/N 4D0407613E) in a vice.

13



It is recommended to produce flats on the hub to improve stability in the vice jaws.





Mount the disc onto the hub using bolts to lock the hub with bolt to enable the controlled tightening of the new fasteners.





#### Front & rear axle.

Replace fasteners 1...10. 15 Replace the fasteners one after the other. Do not loosen and replace more than one fastener at a time! Front axle - 4F0498998F 62 mm 1 Bolt 2 Sleeve **16** 3 Washer Rear axle - 4F0498998E 4 Nut. 45 mm




5	Remove a single fastener.	
6	Fit sleeve (2) and bolt (1) from outside	



Install washer (3) from inside and tighten nut (4) from inside Counterhold bolt.

**Tightening torque: 4 Nm** 





#### **Inside:**

8 Mark nut.




Counterhold bolt and turn nut 90° further (1/4 turn).

9



Replace the fasteners one after the other. <u>Do not loosen</u> and replace more than one fastener at a time!



- **10** Repeat for all discs.
- Please ensure proper braking operation before realising the vehicle to the customer.

Please contact your Area Manager for any further information.

Yours sincerely

Customer Service.

The information and procedures published below are strictly confidential and intended exclusively for authorized operators and individuals. All copyrights are the property of Automobili Lamborghini S.p.A based on copyright law. The company reserves the right to make updates and modifications. The reprinting, reproduction, forwarding to unauthorized people and/or to third parties and partial or entire translation thereof are prohibited without written authorization from Automobili Lamborghini S.p.A.