



To All Lamborghini Dealers and Licensed Service Point
From Customer Service Department
Subject Polishing cycle and materials
Group 140.8.20.00.05.PolishingCycleAndMaterials.GB
Date 09.09.2005
Pages 3

Automobili
Lamborghini S.p.A.

Subject

Recommended polishing cycle and materials for paint scratches repair.

Model / VIN-Range

Gallardo and Murciélago models.

Information to the field

In case you have to remove scratches damaging the paint clear laque, please be informed that the following process and materials are strongly recommended by Automobili Lamborghini.

Important remark: the following polishing cycle is suitable for the removal of scratches only damaging the clear laque, for the repair of deeper scratches it's necessary to repaint completely the part.

Prepare surface for polishing process depending on the specific case needs. If necessary use wet and/or dry abrasive paper finishing with abrasives Abralon P2000 (diam. 150 mm) and Abralon P4000 (diam. 150 mm).

Producer: Mirka (www.mirka.com)

Article number: (P2000) 8A24102095; (P4000) 8A24102097



In case of deep scratches

- 1) Polish the surface using:
 - Wool cloth “Cappuccio Merinos”
Supplier: Ecocolor Engineering (Tel.0039059312277; info@ecocolor.net)
Article number: -
 - Abrasive paste “Eco Shine 100 Media”
Producer: New Chemical (newchemicals.com - info@newchemicals.com)
- 2) Repeat if necessary polishing like described in point 1.
- 3) Polish the surface using:
 - Black soft corrugated sponge “05735-3M”
Producer: 3M (www.3m.com)
Article number: 05735
 - polishing paste Scholl P27
Producer: Scholl Concepts GMBH (Tel. +49 (0) 7141-292990;
Fax +49 (0) 7141-2929910; www.schollautocare.de; info@schollconcepts.com)
Article number: 10442
- 4) Clean accurately removing every trace of the products precedently used with:
 - Isopropanolo 15% solution
Producer: Oldenchemical (Tel. +39-011-945.09.
21 - Fax. +39-011-945.33.22. Email:info@oldenchemical.com)
- 5) Check accurately the surface. If it's necessary, repeat operations at point 1, 2.
- 6) Additional operation only for black, blue and red cars:

Apply manually the following polish paste:
 - Polish Super Glym
Producer: Autoglym (Tel. + 44(0)146267776614; www.autoglym.com)

In case of light scratches

- 1) Polish the surface using:
 - Black soft corrugated sponge “05735-3M”
Producer: 3M (www.3m.com)
Article number: 05735
 - polishing paste Scholl P27
Producer: Scholl Concepts GMBH (Tel. +49 (0) 7141-292990;
Fax +49 (0) 7141-2929910; info@schollconcepts.com)
Article number: 10442

The information and procedures published below are strictly confidential and intended exclusively for authorized operators and individuals. All copyrights are the property of Automobili Lamborghini S.p.A based on copyright law. The company reserves the right to make updates and modifications. The reprinting, reproduction, forwarding to unauthorized people and/or to third parties and partial or entire translation thereof are prohibited without written authorization from Automobili Lamborghini S.p.A.



- 2) Clean accurately removing every trace of the products precedently used with:
 - Isopropanolo 15% solution
Producer: Oldenchemical (Tel. +39-011-945.09.
21 - Fax. +39-011-945.33.22. Email:info@oldenchemical.com)
- 3) Check accurately the surface and, if it's necessary, repeat operations on points 1, 2.
- 4) Additional operation only for black, blue and red cars:

Apply manually the following polish paste:
 - Polish Super Glym
Producer: Autoglym (Tel. + 44(0)146267776614; www.autoglym.com)

NOTE

Before starting every operation of the polishing process the surfaces must be perfectly cleaned from every trace of dirt or materials used during former operations.

Your Area Manager is at your full disposal for further clearing.

Best regards

Customer Service Department