

GROUP	MODEL
Body	2013MY
	Sorento (XM)
NUMBER	DATE
PS257	May 2013




TECHNICAL OPERATIONS

SUBJECT: PANORAMIC SUNROOF DUST SEAL REPLACEMENT

When diagnosing a panoramic sunroof assembly with torn dust seals, refer to the procedure below to replace <u>ONLY</u> the affected dust seals and <u>NOT</u> the panoramic sunroof assembly.

Part No.	Description	QTY
KG310 1301	Seal (RH), Sunroof Dust	1
KG310 1601	Seal (LH), Sunroof Dust	1


Panoramic Sunroof Components:



No.	Description
1.	Glass Panel
2.	Rear Rail Cover Seal
3.	Rear Rail
4.	Dust Seal
5.	Side Molding Panel
6.	Sunroof Frame Assy.

Service Procedure:

- 1. Carefully remove the front and rear roof rack rail trim pieces.
- 2. Remove the roof rack rail.



3. Carefully remove the rear sunroof side molding panel.



- 4. Remove the dust seal by pulling it up and towards the front of the vehicle.
- Clean out any debris, if present, and lubricate the sunroof track using Silicone based grease (P/N UM011 CH052).
- 6. Clean the mounting surface for the dust seal using Isopropyl Alcohol.
- 7. Install the new dust seal.
- 8. Re-install all removed components by reversing the order of removal.

